
Keeping your line up and running



















BELT CONVEYOR PRODUCTS

A comprehensive line of innovative belt conveyor products that address the key issues you face.


FLEXCO

Partners in Productivity

SOLUTIONS FOR EVERY ISSUE ALONG THE BELT LINE



With over 100 years of experience in the belt conveyor industry, Flexco knows that keeping your line running smoothly is essential to the success of your operation. That's why we've developed a comprehensive line of innovative belt conveyor products that address the key issues you face.





Innovative Designs, Superior Engineering, Industry Expertise

Since 1907, we've been dedicated to improving belt performance and productivity. That's meant spending a lot of time in the field, working alongside customers and learning about their everyday challenges—first-hand.

We use that hard-won knowledge to design belt conveyor products that work better and last longer. In fact, we pioneered many of the advanced features that have since become industry standards.



Cleaner Innovations

- Patented, Faceted Blade Profile—These blades continually renew their edges, creating more efficient cleaning
- Better-Performing Tungsten Carbide Cleaner Blades— After years of testing and research, we've created blades that last longer and wear more evenly
- Heavy-Duty Spring Tensioning Systems— An important part of our cleaning systems, our tensioners enable easy visual inspection and maintain proper tension
- "Material Path" Cleaning—This unique option lets you match your cleaner width to your actual material path, reducing differential blade wear
- Larger Diameter Poles—Our poles are designed to resist the powerful twisting forces caused by continuous belt motion



Belt Tracking Innovations

 Pivot-and-Tilt technology—Special sensors detect belt wander, then guide the belt back to the correct path



Impact Bed Innovations


- Velocity Reduction Technology

 —An exclusive feature of our impact beds, this technology deadens impact energy for less rebound and material degradation
- Slide-Out Service[™]—Designed for fast and safe complete bar change-outs



Lagging Innovations

- An 80%-Ceramic Solution—We were the first to market with this option
- Incredibly Fast Installation—Our weld-on lagging is 50% faster to install than other lagging products



Mineline® – When "standard" products just won't do.

Flexco Mineline® products have been designed and engineered to work—day in and day out—in some of the toughest applications in the world. Regardless of the application, whether it be underground coal mining, port loading facilities, or other heavy tonnage applications that test the strength and durability of your conveyor system, Mineline is the answer. Customers have come to expect a Flexco cleaner, impact bed or tracker with the Mineline brand by its name to excel—even in situations where other products have failed.

Next to Mineline

Next to Mineline endorsed products, you'll find this mark:

Flexco Belt Conveyor Products Deliver Benefits for Your Belt—And Your Bottom Line



Budget Savings

- Flexco cleaners and other belt conveyor products increase the life of the belt by reducing wear from carryback, mistracking, and other issues. Given the cost of belting, being able to keep your belts longer can mean substantial savings.
- Our products also help reduce wear on other key conveyor components, like rollers, pulleys, splices, and more. That saves you even more money.
- By cutting down on carryback, spillage, and other belt problems, our products also reduce safety hazards. And as you know, accidents can be costly—in terms of lost productivity and possible fines.



Lower Maintenance Costs

- Because they reduce carryback and spillage, our belt conveyor products cut down on timeconsuming cleanup.
- When your belt and other important conveyor components are protected from damage, you can spend less time making repairs and less money buying replacement components. In fact, studies show that reducing carryback from 3% to 1% can result in a 67% reduction in maintenance costs.



Consistent, Efficient Performance

 Unscheduled shutdowns for maintenance or repairs mean serious production losses. Our belt conveyor products help you maximize uptime by correcting the issues—such as mistracking and carryback that typically cause system damage.



Greater Safety

 Studies show that approximately 42% of conveyorrelated accidents occur during maintenance activities.
 Our cleaners and other belt conveyor products minimize the need for maintenance and reduce the risk of accidents.



Serviceability

- Proper servicing of products, such as belt cleaners and impact beds, is key to ensuring effective and long-lasting performance. That's why all Flexco products are designed with features that make regular servicing easy.
- We are continually enhancing our already servicefriendly products, making them even easier to maintain.

For example, we've added an easy-to-replace blade cartridge to our MHS Heavy-Duty Belt Secondary Cleaner, and Slide-Out Service™ bars to our DRX™ Impact Beds.

YOUR ISSUE: CARRYBACK OUR SOLUTION: ADVANCED CLEANING SYSTEMS

Step 1 Understand Your Options

BELT CLEANERS

Precleaners

- Mounted to the head pulley and below the material flow
- Ideal for removing large pieces of material typically about 60–70% of initial carryback
- Blade width/material path options

Secondary cleaners

- Located just past where the belt leaves the head pulley—and anywhere else down the beltline
- Especially good at removing fines, increasing cleaning efficiency to +90%

BLADE OPTIONS

Polyurethane

- · Easier on the belt
- · Works well with mechanical splices
- Economical
- Specialty formulations for high heat, chemical resistance, or water removal

Tungsten carbide:

- Superior cleaning efficiency
- Long wear



Step 2 10 Key Criteria for Analyzing Your Conveyor System

- 1 Your belt speed and belt width*
- 2 What types of splices are present and their condition*
- 3 Any unusual characteristics of your load or environment (extreme heat, abrasiveness, mud, etc.) —a specialty cleaner that can withstand these conditions may be necessary*
- 4 Whether the belt reverses
- 5 Your conveyor structure width
- 6 Your pulley diameter—typically, the larger the pulley, the larger the required cleaner
- 7 Your pulley condition—if the pulley is worn or not perfectly round, a segmented blade may clean more effectively
- **8** Where you plan to position the cleaner and how much room there is to accommodate it
- 9 The material's path on the belt—matching the cleaner to the material path reduces differential blade wear
- 10 Your desired level of performance and upkeep
- * **Note:** CEMA has created an application classification guide that addresses these three criteria. Further explanation of this is found on Page 7.

Step 3 Determine Whether You Need a Complete Solution

Some operators want their belts as clean as possible; others are comfortable with a certain amount of renegade material.

To achieve maximum cleaning efficiency, it's best to bring together a precleaner and one or more secondary cleaners to form a comprehensive system. If you only want to install a single cleaner, try to target the area—such as the head pulley—where it will have the greatest effect.



APPLICATION CLASSIFICATION GUIDE

CEMA (Conveyor Equipment Manufacturers Association) publishes a guide with the explicit goal of providing "a uniform method for determining the application class of any individual belt cleaner." This is meant as a way to assist in the selection of the correct belt cleaner or belt cleaner system. The complete guide, titled "Classification of Applications for Bulk Material Conveyor Belt Cleaning," or CEMA Standard 576, is available from CEMA.

The classification is built on a points system based on five key criteria. While others play a role as noted on Page 6, these five were chosen as the key elements in selecting the appropriate cleaner or cleaning system. The five criteria are:


- 1. belt width
- 2. belt speed
- 3. splice type
- 4. material abrasiveness
- 5. material stickiness/moisture content

Each of these criteria score points; points increase based on the impact it would have on the required cleaner. Wider belt widths, faster belt speeds, introduction of mechanical splices, increase in material abrasiveness (using CEMA Standard 550), and increasing the moisture content of the material all add to the point totals when scoring an application.

The results of scoring the application created five classes:

Score	Class
<6	1
7–10	2
11–15	3
16–23	4
>24	5

In accordance with this classification, you will find class ratings for Flexco's belt cleaners throughout this guide as another resource to assist you in choosing the correct cleaning system for your application, while keeping in mind the full criteria found on Page 6. For more detailed info on each cleaner, log on to www.flexco.com.



Shown: H-Type® V-Tip Precleaner



Shown: MHS HD Secondary Belt Cleaner



Shown: MDWS Secondary Belt Cleaner




As a wireless platform that transfers data via cloud technology, Flexco Elevate® is remote, real-time monitoring of belt cleaners from an intuitive digital dashboard. Belt cleaners are connected and data insight continually gathered using cutting-edge analytics. Information is transferred to the Elevate Dashboard from state-of-the-art devices attached to every Flexco cleaner throughout the operation. That information combines with maintenance information that is logged via a mobile app to provide predictive data-driven insights direct to your dashboard so you can take action with confidence.


Data Insights Remove Belt Cleaner Guesswork

With the Flexco Elevate® deployment in place, operations will have immediate access to data to easily measure internal efficiencies and monitor productivity.

WHAT THE INTERACTIVE DASHBOARD TELLS OPERATORS:

- Location of installed cleaners at your location and across your operation
- Belt Conveyor System specifications
- Belt Cleaner engagement
- Belt and Cleaner run times
- Urethane and Carbide blade wear
- Belt Cleaner Spring Tensioner reminders
- Abnormal event notification
- Tamper detection
- Detailed Maintenance Logs with exact times and exactly what was done







i3 Devices: 3 unique device types used by geography - US, Australia,

and Global

Dimensions: 200 x 165 x 90 mm (7.875 x 6.375 x 3.5")

Compatible Pole Diameters: 60 mm and 73 mm (2.375" and 2.875") Compatible Cleaner Type: Flexco Precleaners and Secondary Cleaners

Battery Type: Non-rechargeable, lithium-thionyl chloride **Operating Temperature Range:** -30° to 65°C (-22° to 149°F) -20° to 40°C (-4° to 104°F) in explosive environments

Regulatory: FCC (US); RCM (Australia); CE, ISED (Global)

Certifications, Standards: IP66, RoHS (US, Australia and Global) Explosive Environments: IECEx (Australia); MSHA and ATEX

(contact Flexco regarding specific standards)

SECURITY

- End-to-End Security: Encryption layers in OS and in transit
- Wi-Fi Security: WEP, WPA, WPA2
- i3 Mobile App: Permission-based access (only pre-defined authorized users can access portals)
- i3 Dashboard: Permission-based access (only pre-defined authorized users can access portals)
- Data Ownership: All belt cleaner i3 data is wholly owned by the customer


WIRELESS COMMUNICATIONS

- Cellular Communication: LTE CAT-M1 on AT&T (US): LTE CAT-M1 on Telstra (Australia); 2G/3G on AT&T (Global)
- Wi-Fi Communication: 802.11a/b/g/n/ac
- Bluetooth® Wireless Communication: Low energy up to 10 m range

INSIGHT ACCESS

- i3 Mobile App: Android, iOS Compatible
- i3 Dashboard: Optimized for Google Chrome, but accessible via preferred browser

BLADE AND CLEANER OPTIONS



Application Description	EZP-LS	EZP1 (Standard/White)	EZP1 High-Temp	EZP1 UHT	MSP	MSP UHT	ММР
Belt Width*	300–1500 mm (12–60")	300–1800 mm (12–72")	300-1800 mm (12-72")	300–1800 mm (12–72")	600–2100 mm (24–84")	600–1800 mm (24–72")	600–2400 mm (24–96")
Belt Speed**	< 2.5 m/s (500 FPM)	< 3.5 m/s (700 FPM)	< 3.5 m/s (700 FPM)	< 3.5 m/s (700 FPM)	< 3.5 m/s (700 FPM)	< 3.5 m/s (700 FPM)	< 5.0 m/s (1000 FPM)
Head Pulley Diameter	6–22" (150–550 mm)	10–36" (250–900 mm)	10–36" (250–900 mm)	10–36" (250–900 mm)	16-42" (400-1050 mm)	16-42" (400-1050 mm)	16-48" (400-1200 mm)
Temperature Range	-35–82°C (-30–180°F)	-35-82°C (-30-180°F)	< 135°C (275°F) with spikes to 163°C (325°F)	< 200°C (400°F) with spikes to 232°C (450°F)	-35-82°C (-30-180°F)	< 200°C (400°F) with spikes to 232°C (450°F)	-35-82°C (-30-180°F)
Blade	ConShear™ LS	ConShear™	ConShear™	ConShear™	ConShear™	ConShear™	TuffShear™
Reversing Belts	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Work with Mechanical Fasteners	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Application Description	МНР	МНСР	МХР	H-Type® (XF2 & XF)	H-Type [®] (HV & HV2)	High-Temp V-Tip
Belt Width*	600–2400 mm (24–96")	600–2400 mm (24–96")	1050–3000 mm (42–120")	450–1800 mm (18–72")	450–1800 mm (18–72")	450—1200 mm (18—48")
Belt Speed**	< 7.5 m/s (1500 FPM)	< 6.0 m/s (1200 FPM)	< 10.0 m/s (2000 FPM)	< 5.0 m/s (1000 FPM)	< 7.5 m/s (1500 FPM)	< 5.0 m/s (1000 FPM)
Head Pulley Diameter	500–2100 mm (20–84")	500–1200 mm (20–48")	1200–2400 mm (48–96")	250–1175 mm (10–47")	250–1675 mm (10–67")	200–875 mm (8–35")
Temperature Range	-35–82°C (-30–180°F)	-35-82°C (-30-180°F)	-35–135°C (-30–275°F)	-35-82°C (-30-180°F)	-35-82°C (-30-180°F)	< 204°C (400°F) with spikes to 232°C (450°F)
Blade	MegaShear™	SuperShear™	UltraShear™	HXF, HXF2	HV	HV
Reversing Belts	Yes	Yes	Yes	Yes	Yes	Yes
Work with Mechanical Fasteners	Yes	Yes	Yes	Yes	No	No

^{*}Special sizes available upon request.

^{**}Belt speeds can be higher in vulcanized applications.

BLADE AND CLEANER OPTIONS

Secondary Cleaner Options



Application	Y-Type™ SD	Y-Type™ HD	Y-Type [™] UHT	Y-Type™ SD	Y-Type™ HD	EZS2	EZS2	FMS	FMS
Description	Polyurethane	Polyurethane	Polyurethane	Carbide	Carbide	(C-Tip)	High Temp	(C-Tip)	(V-Tip)
Belt Width*	450–1200 mm	900–1800 mm	900–1800 mm	450–1200 mm	900–1800 mm	450–1800 mm	450–1800 mm	450–2100 mm	450–2100 mm
	(18–48")	(36–72")	(36–72")	(18–48")	(36–72")	(18–72")	(18–72")	(18–84")	(18–84")
Belt Speed**	< 3.0 m/s	< 3.8 m/s	< 3.8 m/s	< 3.0 m/s	< 3.8 m/s	< 3.5 m/s	< 3.5 m/s	< 5.0 m/s	< 6.0 m/s
	(600 FPM)	(750 FPM)	(750 FPM)	(600 FPM)	(750 FPM)	(700 FPM)	(700 FPM)	(1000 FPM)	(1200 FPM)
Temperature Range	-35-82°C (-30-180°F)	-35-82°C (-30-180°F)	< 200°C (400°F) with spikes to 232°C (450°F)	-35–82°C (-30–180°F)	-35–82°C (-30–180°F)	-35–92°C (-30–200°F)	< 200°C (400°F) with spikes to 232°C (450°F)	-35–148°C (-30–300°F)	-35–148°C (-30–300°F)
Reversing Belts	Yes	Yes	Yes	Yes	Yes	No	No	No	No
Work with Mechanical Fasteners	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

Application	P-Type®	P-Type®	P-Type® LS	R-Type®	R-Type®	MHS	MHS	U-Type®	U-Type®
Description	(C-Tip)	(V-Tip)	(C-Tip)	(C-Tip)	(V-Tip)	(C-Tip)	(V-Tip)	(F-Blade)	(C-Blade)
Belt Width*	450–1800 mm	450–1800 mm	450–1350 mm	450–1800 mm	450–1800 mm	450-2400 mm	450–2400 mm	450-2100 mm	450–2100 mm
	(18–72")	(18–72")	(18–54")	(18–72")	(18–72")	(18-96")	(18–96")	(18-84")	(18–84")
Belt Speed**	< 5.0 m/s	< 6.0 m/s	< 5.0 m/s	< 5.0 m/s	< 6.0 m/s	< 6.0 m/s	< 7.5 m/s	< 5.0 m/s	< 6.6 m/s
	(1000 FPM)	(1200 FPM)	(1000 FPM)	(1000 FPM)	(1200 FPM)	(1200 FPM)	(1500 FPM)	(1000 FPM)	(1300 FPM)
Temperature Range	-35-82°C								
	(-30-180°F)								
Reversing Belts	No	No	No	Yes	Yes	Yes	Yes	No	No
Work with Mechanical Fasteners	Yes	No	Yes	Yes	No	Yes	No	Yes	Yes

Application Description	MDWS	CFC	CBS™	Chevron	Motorized Brush Cleaner	Belt Driven Brush Cleaner
Belt Width*	450–1800 mm	600–1600 mm	450–2100 mm	450–2100 mm	450–2100 mm	450–2100 mm
	(18–72")	(24-63")	(18–84")	(18–84")	(18–84")	(18–84")
Belt Speed**	< 8.1 m/s	< 2.5 m/s	< 4.0 m/s	< 2.5 m/s	< 3.5 m/s	< 3.5 m/s
	(1600 FPM)	(500 FPM)	(800 FPM)	(500 FPM)	(700 FPM)	(700 FPM)
Temperature Range	-35-82°C	-35-82°C	-30-82°C	-35-82°C	-30-82°C	-30-82°C
	(-30-180°F)	(-30-180°F)	(-20-180°F)	(-30-180°F)	(-20-180°F)	(-20-180°F)
Reversing Belts	No	Yes	No	Yes	No	No
Work with Mechanical Fasteners	Yes	Yes	Yes	Yes	Yes	Yes

^{*}Special sizes available upon request.

^{**}Belt speeds can be higher in vulcanized applications.



FLEXCO PRECLEANERS

EZP-LS "Limited Space" Precleaner

- Compact design with shorter pole length
- Do-it-yourself installation and minimal maintenance
- Standard-duty, solid-blade design

Visual tension check



Specifications:

Maximum Belt Speed*: 2.5 m/s (500 FPM) Pulley Diameter: 150-550 mm (6-22") **Applications**

Brick/Block Plants, Ready Mix Plants, Road/Mobile Equipment

CEMA Class 2

EZP-LS High-Temp

- High-temp blade rated up to 135°C (275°F)
- Can handle temperature spikes to 163°C (325°F)
- Applications: Coke, Clinker, Cement, Asphalt



- White food-grade, chemical-resistant ConShear $^{\!\scriptscriptstyle\mathsf{TM}}$ blade
- Stainless Steel components for superior corrosion resistance
- Applications: Fermentation Byproducts, Preprocessed Foods

EZP1 Precleaner

- Standard-duty, with 60 mm (2-3/8") diameter pole
- Requires just 100 mm (4") of horizontal clearance
- . Do-it-yourself installation and minimal maintenance
- Visual tension check



Specifications:

Maximum Belt Speed*: 3.5 m/s (700 FPM) Pulley Diameter: 250-900 mm (10-36") Applications:

Aggregate, Sand & Gravel, Cement, Wood Processing, Recycling

CEMA Class 3



EZP1

High-Temp





- High-temp blade rated up to 135°C (275°F)
- Can handle temperature spikes to 163°C (325°F)
- Applications: Coke, Clinker, Cement, Asphalt
- Ultra high-temp blade rated up to 200°C (400°F) Can handle temperature spikes to 232°C (450°F)
- Applications: Coke, Clinker, Cement, Asphalt



- White food-grade, chemical-resistant $\mathsf{ConShear}^{\scriptscriptstyle\mathsf{IM}}\,\mathsf{blade}$
- Stainless Steel components for superior corrosion resistance
- Applications: Fermentation Byproducts, Preprocessed Foods



- Compact Torsion Twist Tensioner allows for measurable and verifiable tension
- Tensioner compatible to mount on either end of pole

*Belt speeds can be higher in vulcanized applications.

FLEXCO PRECLEANERS

MSP Standard Mine-Duty Precleaner

- Standard Mine-Duty, with 73 mm (2-7/8") diameter rugged pole design
- Do-it-yourself installation and minimal maintenance
- . Mine-duty, solid blade design
- Highly effective cleaning



Specifications

Maximum Belt Speed*: 3.5 m/s (700 FPM) Pulley Diameter: 400-1050 mm (16-42")

Aggregate, Sand & Gravel, Cement, Wood Processing, Recycling

CEMA Class 3



MSP Ultra High-Temp



- High-temp blade rated up to 200°C (400°F)
- Can handle temperature spikes to 232°C (450°F)
- Applications: Coke, Clinker, Cement, Asphalt

MSP Stainless Steel



- Stainless Steel components for superior corrosion resistance
- Applications: Phosphate, Potash, Salt

MMP Medium Mine-Duty Precleaner

- Medium-duty mining precleaner with TuffShear™ blade
- Heavy-duty, 3-piece design pole with dual tensioners
- Visual tension check



Specifications:

Maximum Belt Speed*: 5.0 m/s (1000 FPM) Pulley Diameter: 400-1200 mm (16-48")

Underground Mining, Hard Rock Mining, Steel Mills, Iron Ore, Metal Mining, Aggregate, Coal-Fired Power Plants, Load-out Facilities

CEMA Class 4



MMP Stainless Steel



- Stainless Steel components for superior corrosion resistance
- Applications: Phosphate, Potash, Copper/Gold Mining, Salt, Load-out Facilities Near Salt Water

MHP Heavy-Duty Precleaner

- Heavy-duty, solid blade precleaner
- Heavy-duty, 3-piece design pole with rugged, dual spring tensioners
- Abrasion-resistant, XL solid polyurethane MegaShear™ blade




Applications:

Underground Mining, Hard Rock Mining, Metal Mining, Longwall Coal Mining, Steel Mills, Iron Ore

CEMA Class 5

MHCP Heavy-Duty Cartridge Precleaner

- One of the most rugged precleaners available
- Engineered for abusive conditions
- Telescoping 3-piece pole that resists twisting/bowing/bending
- Quick-change SuperShear™ blade cartridge for fast, easy maintenance



Underground Mining, Hard Rock Mining, Metal Mining, Longwall Coal Mining, Steel Mills, Iron Ore

CEMA Class 5





^{*}Belt speeds can be higher in vulcanized applications.

FLEXCO PRECLEANERS Continued

H-Type® HV/HVP Precleaner

- Tungsten carbide tip provides superior cleaning efficiency (vulcanized belts only)
- Segmented blades work independently
- Visual tension check





Optional HV Protected Tips

Specifications.

Maximum Belt Speed*: 7.5 m/s (1500 FPM) Pulley Diameter: 250-1575 mm (10-63")

Power Plants, Port Facilities, Hard Rock Mining, Steel Mills, Iron Ore

CEMA Class 4

HV2 Precleaner

- Tungsten carbide tip provides superior cleaning efficiency (vulcanized belts only)
- 150 mm (6") segmented blades work independently
- Adjustable cushions allow for enhanced pulley conformance
- Visual tension check



Specifications:

Maximum Belt Speed*: 7.5 m/s (1500 FPM) Pulley Diameter: 250-1675 mm (10-67") Applications:

Power Plants, Port Facilities, Hard Rock Mining, Steel Mills, Iron Ore

CEMA Class 4

H-Type® HV/HVP Stainless Steel



STAINLESS STEEL

- Stainless Steel components for superior corrosion resistance
- Applications: Phosphate, Potash, Salt

H-Type® High-Temp HV Precleaner

- Tungsten carbide tip provides superior cleaning efficiency (vulcanized belts only)
- Segmented blades work independently
- Adjustable cushions allow for enhanced pulley conformance
- Visual tension check



Specifications:

Maximum Belt Speed*: 5.0 m/s (1000 FPM) Pulley Diameter: 250-1575 mm (10-63") Applications:

Power Plants, Port Facilities, Steel Mills, Iron Ore

CEMA Class 3

H-Type® HXF2 Precleaner

- Suitable as a stand-alone cleaner in standard and medium-duty applications
- Available with polyurethane



Specifications:

Maximum Belt Speed*: 5.0 m/s (1000 FPM) Pulley Diameter: 250-1325 mm (10-53") Applications:

Underground Mining, Hard Rock Mining, Metal Mining, Aggregate

CEMA Class 4





FLEXCO PRECLEANERS

MXP Extreme-Duty Precleaner

- Flexco's largest, most rugged precleaner takes on the harshest mining applications
- 150 and 300 mm (6 and 12") blade segments are easily configured to match material path
- Robust 175 mm (7") diameter pole ends telescope into 200 mm (8") center pole and bolt in place
- Dual spring tensioners allow tension to be visually inspected



Specifications:

Maximum Belt Speed*: 10.0 m/s (2000 FPM) Pulley Diameter: 1200-2400 mm (48-96") Applications:

Underground Mining, Hard Rock Mining, Metal Mining, Aggregate

CEMA Class 5



*Belt speeds can be higher in vulcanized applications.

Applications listed are intended to identify where each cleaner is commonly and most effectively utilized. Belt conditions, belt speeds, and pulley diameters should all be considered before making a final product selection. Consult Flexco to assess specific applications and recommendations.

PAT Pneumatic Air Tensioner

- PAT ensures constant tension for full blade life with little maintenance
- Works with Flexco mechanical fasteners
- Usable with air, nitrogen or water
- Featured on Mineline $^{\bar{s}}$ -approved cleaners like MMP, MHP, MHCP, MHS, CBS $^{\rm m}$, and MDWS
- Can be configured as specials on many other cleaners





FLEXCO SECONDARY CLEANERS

Y-Type™ Secondary Belt Cleaner – Polyurethane Blades

- Segmented tips easily serviced utilizing a removable cartridge
- Spring tensioned to deliver optimal cleaning performance and blade life
- Food grade/chemical resistant polyurethane option available
- Compatible with reversing belts
- Standard-duty (belt widths 450-1200~mm (18–48"))
- Heavy-duty (belt widths 900-1800 mm (36-72"))



Y-Type[™] HD

Maximum Belt Speed: 3.75 m/s (750 FPM)

Applications: Aggregate, Sand & Gravel, Cement

CEMA Class 3



- White food-grade, chemical-resistant blade
- Applications: Preprocessed Foods

CEMA Class 2

Y-Type™ HD **Food Grade**

- White food-grade, chemical-resistant blade
- Maximum Belt Speed: 3.75 m/s (750 FPM)
- Applications: Preprocessed Foods

CEMA Class 3



- - Can handle temperature spikes to 232°C (450°F)
 - Applications: Coke, Clinker, Cement, Asphalt

CEMA Class 2



Y-Type™ HD **Ultra High-Temp**

Y-Type™ Standard **Ultra High-Temp**

- Ultra high-temp blade rated up to 200°C (400°F)
- Can handle temperature spikes to 232°C (450°F)
- Maximum Belt Speed: 3.75 m/s (750 FPM)
- Applications: Coke, Clinker, Cement, Asphalt

CEMA Class 3

*Belt speeds can be higher in vulcanized applications.

FLEXCO SECONDARY CLEANERS Continued

Y-Type[™] Secondary Belt Cleaner — Carbide Blades

- Segmented tungsten carbide blades compatible with mechanical fastener applications are easily serviced utilizing a removable cartridge
- . Spring tensioned to deliver optimal cleaning performance and blade life
- Compatible with reversing belts
- Standard-duty (belt widths 450-1200 mm (18-48")) Heavy-duty (belt widths 900-1800 mm (36-72"))





Y-Type[™] HD

Specifications:

Maximum Belt Speed*: 3 m/s (600 FPM) Applications:


Aggregate, Sand & Gravel, Cement, Light Mining


CEMA Class 3



EZS2 Secondary Belt Cleaner

- Patented FormFlex™ cushions that maintain optimal belt contact
- Do-it-yourself installation
- Segmented tungsten carbide blades
- **Bolt-up tensioning system**





Maximum Belt Speed: 3.75 m/s (750 FPM)

Applications: Aggregate, Sand & Gravel, Cement, Mining

Specifications:

Maximum Belt Speed*: 3.5 m/s (700 FPM) Applications:

Aggregate, Sand & Gravel, Cement

CEMA Class 3



P-Type® Secondary Belt Cleaner

- . Available with C-Tips for mechanical fastener applications or V-Tips for vulcanized applications
- Limited Space model option for telescoping, stacking, or portable conveyors
- Segmented tungsten carbide blades



Specifications:

Maximum Belt Speed*: C-Tip: 5.0 m/s (1000 FPM) V-Tip: 6.0 m/s (1200 FPM)

Applications:

Aggregate, Sand & Gravel, Cement, Wood Processing, Light Mining, Power Plants with Vulcanized Belts

CEMA Class 4

R-Type® Reversing Secondary Belt Cleaner

- Available with C-Tips for mechanical fastener applications or V-Tips for vulcanized applications
- Two-way cushions that accommodate reversing belts
- Do-it-yourself installation
- **Bolt-up tensioning system**



Specifications:

Maximum Belt Speed*: C-Tip: 5.0 m/s (1000 FPM) V-Tip: 6.0 m/s (1200 FPM)

Applications:

Aggregate, Sand & Gravel, Cement, Wood Processing, Light Mining, Recycling, Power Plants with Vulcanized Belts

CEMA Class 4



^{*}Belt speeds can be higher in vulcanized applications.

FLEXCO SECONDARY CLEANERS Continued

FMS Secondary Belt Cleaner

- · Cleaning efficiency of segmented tungsten carbide blades
- Available with C-Tips for mechanical fastener applications or V-Tips for vulcanized applications

Cushion rated temperatures up to 148°C (300°F)



Specifications.

Maximum Belt Speed*: C-Tip: 5.0 m/s (1000 FPM) V-Tip: 6.0 m/s (1200 FPM)

Applications:

Underground Mining, Hard Rock Mining, Metal Mining, Aggregate, Load-out Facilities, Iron Ore, Steel Mills, Power Plants

MHS Heavy-Duty ESAC Secondary Belt Cleaner

- Service Advantage Cartridge™ feature allows for easy service and inspection
- Segmented blades with choices of tungsten carbide tips
- Patented PowerFlex™ cushions maintain optimal belt contact



Specifications:

Maximum Belt Speed*: C-Tip: 6.0 m/s (1200 FPM) V-Tip: 7.5 m/s (1500 FPM)

Applications:

Underground Mining, Hard Rock Mining, Metal Mining, Aggregate, Load-out Facilities, Iron Ore, Steel Mills, Power Plants

CEMA Class 5

MHS Heavy-Duty Secondary Belt Cleaner

- Segmented blades with choices of tungsten carbide tips
- Patented PowerFlex™ cushions maintain optimal belt contact
- Two-way cushions available for reversing applications that roll back, or tripper and stacker applications
- Tensioners and cushion create 4-points of relief, making the cleaner fastener-friendly



Specifications:

Maximum Belt Speed*: C-Tip: 6.0 m/s (1200 FPM) V-Tip: 7.5 m/s (1500 FPM) Tensioner

Underground Mining, Hard Rock Mining, Metal Mining, Aggregate, Load-out Facilities, Iron Ore, Steel Mills, Power Plants

CEMA Class 5

Optional SAT XD

MHS HD Stainless Steel

- Stainless Steel components for superior corrosion resistance
- Applications: Salt, Copper/Gold Mining, Phosphate, Potash, Load-out Facilities

U-Type® Secondary Belt Cleaner

- U-shaped blade and offset pole that intensify cleaning power
- Blade replacement made easy with removable front plate
- Works best in wet applications, cupped belts, and belts with worn centers
- Choice of standard or impact-resistant tungsten carbide, or polyurethane blades
- Blade tips scrape off carryback, while rubber backers "squeegee" wet material



Specifications.

Maximum Belt Speed*: C-Tip: 6.6 m/s (1300 FPM)

Applications:

Cement, Coal Mining, Coal Prep Plants, Power Plants, Load-out Facilities

CEMA Class 5

U-Type® Stainless Steel

- Stainless Steel components for superior corrosion resistance
- Applications: Power Plants, Load-out Facilities

FLEXCO SECONDARY CLEANERS Continued

CBS™ Continuous Blade Secondary™ Belt Cleaner

- The thin, hard edge of the metal blade delivers high cleaning efficiency and long wear life.
- Made from heavy-duty, corrosion-resistant steel, and available in sizes for belt widths from 450-2400 mm (18-96"). Additional sizes are available upon request.
- When the CBS™ is teamed with the MMP Precleaner the system provides maximum cleaning power for tough applications.
- All service can be performed from a safe position at the side of the conveyor.



Specifications:

Maximum Belt Speed*: Mechanical Fasteners: 4.0 m/s (800 FPM) Vulcanized Belts: 6.0 m/s (1200 FPM)

Applications:

Underground Mining, Hard Rock Mining, Metal Mining, Aggregate, Load-out Facilities, Iron Ore, Steel Mills, Power Plants

CEMA Class 4



CBS™ with Curved Blade

Curved blade for worn or cupped belts.

Applications: Underground Mining, Hard Rock Mining, Metal Mining, Aggregate, Load-out Facilities, Iron Ore, Steel Mills, Power Plants

MDWS DryWipe Secondary Belt Cleaner

- Removes excess water to ensure a dry return trip down the belt line
- Do-it-yourself installation and minimal maintenance
- Ideal for systems using a water spray pole



CEMA Class 4



CFC Secondary Belt Cleaner

- Flexible, polyurethane finger blades can handle chevron or cleat heights up to 32 mm (1-1/4")
- Available for belt widths: 600-1600 mm (24-63").
- Works with mechanically spliced or vulcanized belts



Specifications:

Maximum Belt Speed*: 2.5 m/s (500 FPM) Applications Wood Chipping, Sand

CEMA Class 3



Motorized Brush Cleaner

- Uniquely patterned bristles aid in reducing material buildup and clogging
- Adjustable tensioners allow easy brush-to-belt adjustment as the bristles wear
- Spins opposite the belt direction for optimal cleaning
- Do-it-yourself installation and quick drum replacement



Specifications:

Maximum Belt Speed*: 3.5 m/s (700 FPM) Applications: Wood Chipping, Sand

CEMA Class 4



Belt Driven Brush Cleaner

- Self-driven system uses belt energy to drive the cleaner
- The brush spins opposite of the belt direction for optimal cleaning
- Unique patterned bristles aid in reducing material build up
- Tensioners allow for easy brush-to-belt adjustments as the bristles wear



Specifications:

Maximum Belt Speed*: 3.5 m/s (700 FPM) Applications

Wood Chipping, Sand

CEMA Class 4



^{*}Belt speeds can be higher in vulcanized applications.

FLEXCO SECONDARY CLEANERS Continued

Chevron Secondary Belt Cleaner

- For raised top, chevron, or grooved belts
- Hundreds of rubber fingers that flick off carryback
- · Free-rotating design that works only when the belt runs
- Do-it-yourself installation and quick drum replacement



Specifications:


Maximum Belt Speed*: 2.5 m/s (500 FPM)
Applications:
Wood Chipping, Sand

CEMA Class 3




Wash Box

- Complete stainless steel construction
- Modular design for a simpler installation
- · Center or rear drain options



*Belt speeds can be higher in vulcanized applications.

Applications listed are intended to identify where each cleaner is commonly and most effectively utilized. Belt conditions, belt speeds, and pulley diameters should all be considered before making a final product selection. Consult Flexco to assess specific applications and recommendations.



FLEXCO BELT CLEANER ACCESSORIES



Mounting Plate Kit

incl. 2 plates, 400 x 800 mm (16 x 32")

- For use with Mounting Bars to mount cleaners on open head pulleys
- For use with MSP, MMP, MHP, MHCP



SST Mounting Bracket Kit

- For MHS or MDWS secondary cleaner installs requiring additional mounting versatility
- Long mounting bracket kit also available for installations that require extra length legs



Optional Mounting Bar Kit

incl. 8 bolts, nuts and washers

- For mounting precleaners on open head pulleys
- Weld on both sides of pulley and bolt on steel plates
- For use with MSP, MMP, MHP, MHCP



Brush Cleaner Drop Bracket Kit

• For brush cleaner installations that require extra length legs



Optional Top Angle Kit

 Used with both Standard and Long SST Mounting Bracket Kits for additional mounting options



YST Mounting Bracket Kit

• For Y-Type™ Secondary Belt Cleaner installs requiring additional mounting versatility



Inspection Door

- Lockable design
- Dust-tight sea
- Available in 300 x 300, 300 x 450, 450 x 600, and 600 x 600 mm (12 x 12, 12 x 18, 18 x 24, and 24 x 24")
- · Available with or without screen



Pole Extender Kit

- Provides 750 mm (30") of extended pole length
- Includes 2 pole extenders



Stabilizing Rollers

- For use in applications with belt cup or belt flap
- By preventing these issues secondary cleaner performance and blade/tip life is enhanced



Water Spray Pole Kit

- Stainless steel pole with powder coated steel clamp brackets
- For use with secondary cleaners for an exceptionally clean belt
- Typical pressure setting is 276–414 kPa (40–60 PSI)





Spring Covers and Tensioner Locks

(for Precleaners and Secondaries)

- Spring Covers protect spring and threaded rod from contamination and material buildup
- Tensioner Lock prevents unauthorized cleaner retensioning

YOUR ISSUE: BELT MISTRACKING OUR SOLUTION: BELT TRAINERS

To select the right belt trainer, you need to consider whether:

- The belt is wandering to one or both sides
- The mistracking is happening consistently or occasionally
- The top or return side of the belt is affected
- The belt has a low, medium or high running tension

Use the following chart to identify the best Flexco belt trainer for your needs.

Conveyor Criteria	Belt Positioner™	PTEZ™	PT Smart™	PT Max™	PT Max™ Heavy Duty	PT Max™ Super Duty
Top side mistracking	No	No	No	Yes	Yes	Yes
Return side mistracking	Yes	Yes	Yes	Yes	Yes	Yes
Reversing belts	Yes	Yes	No	No	No	No
Belt mistracking to one side	Better	Better	Better	Better	Better	Better
Belt mistracking to both sides	Acceptable	Better	Best	Best	Best	Best
Inconsistent tracking problem	Good	Better	Best	Best	Best	Best
Belt is cupped (heavy)	Best ‡	Better ‡	Better	Better	Better	Better
Belt has edge damage	Best	Best	Good	Good	Good	Good
Ease of installation	Best	Better	Good	Good	Good	Good
Belt has low running tension	Good	Good	Good	Good	N/A	N/A
Belt has medium running tension	Better	Better	Better	Best	Best	Best
Belt has high running tension	N/A	N/A	N/A	Better	Best	Best
Approx. "upstream" effect*	15 M (50')	6 M (20')	6 M (20')	15 M (50')	15 M (50')	15 M (50')
Approx. "downstream" effect*	15 M (50')	30–36 M (100–120')	36–45 M (120–150')	45–61 M (150–200')	45–61 M (150–200')	45–61 M (150–200')

[‡] Installed on clean side of return belt

FLEXCO BELT TRAINERS

FEATURES & APPLICATIONS

Belt Positioner[™]

- Simple solution for belts wandering to a single side
- Fixed, angled rollers "funnel" the belt onto the correct path
- Available with steel or rubber-lagged rollers
- Return-side installation only
- Easy to install and maintain



Specifications:

Maximum Belt Tension: Small, Medium and Large: 900 PIW; Extra-Large: 1200 PIW Belt Width: 450–2400 mm (18–96")

^{*} Typical results; actual results may vary

FLEXCO BELT TRAINERS

PTEZ™ Belt Trainer

- Polyurethane roller cover to ensure long-lasting performance
- Tapered roller ends drive "pivot and tilt" mechanism to correct mistracking
- Easy to install on one-way and reversing belts
- Versatile mounting options, can be installed on clean side of return belt if cupped





- Maximum Belt Tension: 2400 PIW
- Belt Widths: 1050-2100 mm (42-84")

PT Smart[™] Belt Trainer

- Sensor rollers detect wander, then "pivot and tilt" belt into place
- **Economical solution for medium-tension belts**
- Effectively prevents belt from damaging structure
- Specially designed to fit underground conveyors
- Easy to install



Belt Widths: 450-1800 mm (18-72")

PT Max™ Top Side Belt Trainer

- Sensor rollers detect wander, then "pivot and tilt" belt into place
- Ideal solution for cupped and high-tension belts
- Performs in wet and dry conditions
- Top-side installation only



Heavy-Duty PT Max[™] Top Side

Ideal for high-tension belts

Specifications:

Maximum Belt Tension: 6000 PIW Belt Widths: 1350-2100 mm (54-84")

Super-Duty PT Max™ Top Side

· For highest-tension applications

Specifications:

Maximum Belt Tension: 10,000 PIW Belt Widths: 1800-3000 mm (72-120")

PT Max™ Return Side Belt Trainer

- Sensor rollers detect wander, then "pivot and tilt" belt into place
- Ideal solution for cupped and high-tension belts
- Performs in wet and dry conditions
- Return-side installation only



Heavy-Duty PT Max™ Return Side

• Ideal for high-tension belts

Specifications:

Maximum Belt Tension: 6000 PIW Belt Widths: 1350-2100 mm (54-84")


Super-Duty PT Max™ Return Side

For highest-tension applications

Specifications:


Maximum Belt Tension: 10,000 PIW Belt Widths: 1800-3000 mm (72-120")

YOUR ISSUE: LOAD-POINT SPILLAGE OUR SOLUTION: IMPACT BEDS, SLIDER BEDS, SKIRTING SYSTEMS, PLOWS & MORE



Flexco offers beds for numerous impact ratings:

Up to 25 kg/m (200 lb/ft): EZSB-I, EZIB-L, MSB, DRX[™] 200 25 to 100 kg/m (200 to 750 lb/ft): EZIB-M, DRX[™] 750 100 to 200 kg/m (750 to 1500 lb/ft): MIB, DRX[™] 1500 200 to 400 kg/m (1500 to 3000 lb/ft): DRX[™] 3000 200 to 600 kg/m (1500 to 4500 lb/ft): DRX[™] 4500



How to Select the Right Impact Bed

Step 1:

Calculate Your Impact Energy

Identify the weight of your largest lump size and multiply this number by your drop height. The result, expressed in kg/m (lb/ft), will be your estimated impact energy.

Step 2:

Match the Result to the Bed Rating

No Impact: EZSB-C

Up to 27 kg/m (200 lb/ft): DRX™ 200, MSB, EZSB-I, EZIB-L

27-103 kg/m (200-750 lb/ft): DRX™ 750, EZIB-M

103-207 kg/m (750-1500 lb/ft): DRX™ 1500, MIB

207-414 kg/m (1500-3000 lb/ft): DRX™3000

207-622 kg/m (1500-4500 lb/ft): DRX™ 4500

Material Reference Table

Material	kg/m³	lb/ft³
Coke	657	41
Fertilizer	961	60
Bauxite, crushed	1281	80
Potash	1281	80
Coal, Bituminous, Solid	1345	84
Coal, Anthracite, Solid	1505	94
Slag, Solid	2114	132
Chromium Ore	2162	135
Halite (Salt), Solid	2322	145
Phosphorus	2338	146
Stone (Common, Generic)	2515	157
Limestone, Solid	2611	163
Shale, Solid	2675	167
Granite, Solid	2691	168
Gypsum, Solid	2787	174
Trap Rock, Solid	2883	180
Dolomite, Solid	2899	181
Malachite (Copper Ore)	3860	241
Platinum Ore	4293	268
Hematite (Iron Ore)	5158	322

Sample Calculation

Gather data for your Impact Energy Calculation:

- Q: What size material are you running?
- A: I'm running 203 mm (8") minus limestone.
- **Q**: Is that the largest piece you've seen or could a larger piece get through that 203 mm (8") crusher setting?
- A: Yes, that's the crusher setting; the largest rock I've seen is 203 x 406 x 406 mm (8 x 16 x 16").

Lump Weight (W)

Limestone Material Density = 2611 kg/m³ (163 lb/ft³)

Volume = $\frac{203}{1000} \times \frac{406}{1000} \times \frac{406}{1000} = 0.033 \text{ m}^3 (8/12 \times 16/12 \times 16/12 = 1.185 \text{ ft}^3)$

 $W = 2611 \times 0.033 = 87 \text{ kg} (163 \times 1.185 = 193 \text{ lb})$

- Q: What's the fall height from the top of the feeding conveyor to the receiving belt?
- **A:** There's a 1.5 m (5') drop from the feeding conveyor to a rock box, then another 1.2 m (4') drop to the receiving belt.

Drop Height (H)

H = 1.5 m + 1.2 m = 2.7 m (5' + 4' = 9')

Impact Energy Calculation:

Lump Weight (W) x Drop Height (H) = Impact Energy

 $87 \times 2.7 = 235 \text{ kg/m} (193 \text{ lb} \times 9 \text{ ft} = 1737 \text{ lb/ft})$

This impact scenario would require a DRX™ 3000 or DRX™ 4500.

FLEXCO IMPACT BEDS

FEATURES & APPLICATIONS

Flexco Slider Bed (EZSB-C)

- Uses standard idlers in center section
- Features adjustable trough frames for use on 20°, 35°, or 45°
- Recommended for non-impact sealing areas
- Available with short lead time



Bed Ratina: No impact

Maximum Belt Speed: 5.0 m/s (1000 FPM)

Applications:

Sealing of extended load zone

Flexco Slider Impact Bed (EZSB-I)

- Uses impact idlers in center section
- \bullet $\;$ Features adjustable trough frames for use on 20°, 35°, or 45°
- Recommended for -100 to -150 mm (-4 to -6") materials
- Available with short lead time



Specifications:

Bed Rating: Up to 27 kg/m (200 lb/ft)
Maximum Belt Speed: 5.0 m/s (1000 FPM)
Applications:

Sand and Gravel

FLEXCO IMPACT BEDS

Flexco Standard-Duty Impact Bed (EZIB-L)

- Features adjustable trough frames for use on 20°, 35°, or 45°
- Recommended for light-impact applications
- Recommended for -100 to -150 mm (-4 to -6") materials
- Available with short lead time



Bed Rating: Up to 27 kg/m (200 lb/ft) Maximum Belt Speed: 5.0 m/s (1000 FPM) Applications:

Sand and Gravel

Modular Slider Bed (MSB)

- All bars feature 25 mm (1") UHMW for long wear life
- All bars are chamfered to work with reversing belts
- Recommended for -100 to -150 mm (-4 to -6") materials
- Adjustable trough angle 20°, 35°, or 45°
- Quick and easy service with slide-out trough and center section removal



Seamlessly combine slider and impact beds for ultimate performance

Flexco Medium-Duty Impact Bed (EZIB-M)

- Features adjustable trough frames for use on 20°, 35°, or 45°
- For medium-impact applications
- Recommended for -200 to -250 mm (-8 to -10") materials
- Available with short lead time



Bed Rating: 27-103 kg/m (200-750 lb/ft) Maximum Belt Speed: 5.0 m/s (1000 FPM)

Applications:

Hard Rock Mining, Limestone Quarrying

Modular Impact Bed (MIB)

- All bars feature 25 mm (1") UHMW for long wear life
- All bars are chamfered to work with reversing belts
- Recommended for -300 mm (-12") materials
- Adjustable trough angle 20°, 35°, or 45°
- Sectional slide-out service allows for service alongside the conveyor
- Outer slider bar to seal the load zone







Specifications:

Bed Rating: Up to 27 kg/m (200 lb/ft) Maximum Belt Speed: 5.0 m/s (1000 FPM) Applications:

Sand and Gravel

Specifications:

Bed Rating: Up to 200 kg/m (1500 lb/ft) Maximum Belt Speed: 5.0 m/s (1000 FPM)

Hard Rock Mining, Limestone Quarrying, Load-out Facilities

DRX™200 Impact Bed

- Exclusive Velocity Reduction Technology™ that deadens rebound forces for reduced spillage and material degradation
- Recommended for -100 to -150 mm (-4 to -6") materials
- Slide-Out Service™ for easy maintenance



Bed Rating: Up to 27 kg/m (200 lb/ft) Maximum Belt Speed: 5.0 m/s (1000 FPM) Applications:

Sand and Gravel

DRX™750 Impact Bed

- Exclusive Velocity Reduction Technology™ that deadens rebound forces for reduced spillage and material degradation
- For medium-impact applications
- Recommended for -200 to -250 mm (-8 to -10") materials
- Provides a unique second level of impact relief



Specifications:

Bed Rating: 27-103 kg/m (200-750 lb/ft) Maximum Belt Speed: 5.0 m/s (1000 FPM)

Hard Rock Mining, Limestone Quarrying

FLEXCO IMPACT BEDS Continued

DRX™1500 Impact Bed

- Exclusive Velocity Reduction Technology™ that deadens rebound forces for reduced spillage and material degradation
- · For high-impact applications
- Recommended for -300 mm (-12") materials
- Isolation Mounts ensure a second level of impact force reduction



Bed Rating: 103–207 kg/m (750–1500 lb/ft)
Maximum Belt Speed: 5.0 m/s (1000 FPM)

Applications:

Coal-Fired Power Plants, Coal Prep Plants, Load-out Facilities

DRX[™]4500 Dynamic Impact Bed

- Exclusive Velocity Reduction Technology™ that deadens rebound forces for reduced spillage and material degradation
- For extreme-impact applications requiring the highest energy absorption
- Impact Energy Absorbers compress up to 75 mm (3") to disperse immense amounts of impact energy



Specifications:

Bed Rating: 400-600 kg/m (3000-4500 lb/ft)
Maximum Belt Speed: 5.0 m/s (1000 FPM)

Applications:

Any operation that combines large material size and extreme height

DRX™3000 Dynamic Impact Bed

- Exclusive Velocity Reduction Technology[™] that deadens rebound forces for reduced spillage and material degradation
- For extreme-impact applications requiring high energy absorption
- Impact Energy Absorbers disperse an immense amount of impact energy
- Stationary skirt support bar system helps ensure a positive seal with the skirt rubber



Specifications:

Bed Rating: 207-414 kg/m (1500-3000 lb/ft)
Maximum Belt Speed: 5.0 m/s (1000 FPM)

Applications:

Any operation that combines large material size and extreme height

Adjustable Idler Frame

- · For use around load zone to lift belt off beds
- Features adjustable trough frames in 5° increments
- Useful for transition area



Specifications:

Idler Rating: Standard Roll: No impact

Impact Roll: 27 kg/m (200 lb/ft)

Applications

For use between every two Flexco beds, transitions

Belt Support Bar


- Support from the underside of the belt
- Versatile adjustments with the base, top, and telescoping tube
- Simple installation by bolt-on or welding
- Fits anywhere you have idler gaps between 400-750 mm (16-30")



Specifications:

Applications:

For use between idlers in the sealing zone (after impact)



Applications listed are intended to identify where each impact bed is commonly and most effectively utilized. Material size, lump weight and drop height should all be considered before making a final product selection. Consult Flexco to assess specific applications and recommendations.


FLEXCO SKIRTING SYSTEMS

Specially designed to create an effective seal at load points without damaging the top cover of your belt, our skirting systems are a smart way to improve throughput.

Flex-Seal™ Skirting System

- Dynamic containment unit that fully seals the loading zone
- Sturdy, corrosion-resistant components that deliver long service life
- Easy to install and maintain











Weld-on PAL Pak Bolt-on PAL Pak

- PAL PAK options for safe, easy-toinstall skirt clamps
- Bolt-on version provides no-weld solution to eliminate sparking risks



Versatile design that can be installed on vertical or perpendicular skirt boards

Specifications:

Module Sizes: 1200 mm (4')

Skirting Sizes: 150 mm (6") wide and 8-19 mm (5/16-3/4") thick

Specifications:

Module Sizes: 1200 mm (4')

RMC1 Skirt Clamps

Simple installation, no-hassle maintenance

Interlocking clamp plates and 1200 mm (4') clamp bar

Skirting Sizes: Range of skirt rubber heights; 8-19 mm (5/16-3/4") thick

Flex-Lok™ Skirt Clamps

- Heavy-duty applications
- Strong restraining bar that is held in place by clamp plates to allow easy adjustment of skirt rubber
- Anti-vibration clamp pin can be unlocked with a rubber hammer
- Mini Flex-Lok™ option available—overall height of 40 mm (5-1/2")
- Easy to install and maintain





Specifications:

Module Sizes: 1800 mm (6')

Skirting Sizes: Skirt rubber 8-25 mm (5/16-1") thick

Skirt Wear Liner Kits

- Combines new liner wall with existing Flexco Skirting Kits to provide an upgraded sealing edge
- Wear liner adjustable from outside the chute for quick and easy service
- Straight and tangent kits with long wearing 6 mm (1/4") AR400 plate or 25 mm (1") Polyurethane Canoe Liner options available
- Stops material loss, eliminates safety hazards, and reduces wear on conveyor components



Liner Height: 368 mm (14-1/2") Liner Length: 1200 mm (4')

Polyurethane Skirting

- Polyurethane skirting offers a more wear-resistant material than typical rubber
- Lower coefficient of friction reduces strain on the system
- Works with Flexco's skirt clamp options that offer simple serviceability
- 35° chamfer eliminates the typical skirting break-in period
- Soft durometer (65A) polyurethane with exceptional tear resistance to ensure a good seal and long belt life



Standard Skirting



Dual Seal Skirting

Specifications:

Temperature Range: -30° to 82°C (-20° to 180°F)

Enclosed Skirting System

- Easy installation
- Seal skirting to your conveyor belt using vertical or tangential sealing options
- Rear door seal provides easy access for wash-down, inspection or repairs
- Dust curtains control air flow throughout the system to keep dust levels low Adjustable liners provide increased skirt liner life



How to Select the Right Belt Plow

When choosing a plow to prevent fugitive material from finding its way into your tail pulley, you need to consider where you want to discharge any debris.

To discharge material to a single side of the belt:

Choose the RDP1 Diagonal Plow of MXDP.

To discharge material to both sides of the belt:

Choose the V-Plow or MXDP.

FLEXCO PLOWS

FEATURES & APPLICATIONS

Flexco offers two advanced plows that prevent costly damage to tail pulleys and gravity take-ups, while cleaning the inside of the belt.

RDP1 Diagonal Plow

- Discharges debris to one side of belt
- · Unique angled blade that creates effective "spiral" action
- Fixed position eliminates bouncing and vibration problems
- Appropriate for use at any point along inside of return belt
- Simple and quick installation and blade replacement



Specifications:

Maximum Belt Speed: 3.5 m/s (700 FPM) Belt Widths: 450-2100 mm (18-84")

V-Plow

- Simultaneously discharges debris to both sides of belt
- Angled blade design "spirals" away debris and water
- Easy to install and maintain
- Fits virtually any conveyor structure
- Turnbuckle at nose allows for fine-tuning at installation




Specifications

Maximum Belt Speed: 5.0 m/s (1000 FPM) Belt Widths: 450-2400 mm (18-96")

MXDP Diagonal Plow

- Solid construction and over-sized hardware for added durability
- New adjusting glide minimizes vibration and provides impact absorption
- Over-sized polyurethane blade for long-lasting wear
 Curved frame provides added strength
- Optional Hungry Board protects against bouncing material



YOUR ISSUE: SLIPPAGE OUR SOLUTION: PULLEY LAGGING

How to Select the Right Lagging Product

To select the right pulley lagging, be sure to consider the environmental conditions around the pulley:

- · Belt condition, i.e., wet or dry
- The service required for bonded lagging versus weld-on
- The expected wear life of the lagging

Use the following chart to identify the best Flexco lagging for your needs

	Calcal Built			or your mod	经制度的					
		Flex-Lag® Rubber		l l	Flex-Lag® Cerami	C	Flex-Lag®	Weld-On™		
Criteria	Light Duty	Plain	Diamond	Diamond Pattern	Medium Ceramic	Full Ceramic	Rubber Diamond	Full Ceramic		
Total Thickness*	7.5 mm (5/16")	10–25 mm (3/8–1")	10–25 mm (3/8–1")	12 mm (1/2")	15 mm (5/8")	12.7 mm (1/2")	14 mm (9/16")	15 mm (5/8")		
Belt Width*	Any Width	Any Width	Any Width	Any Width	450–2100 mm (18–84")	450–2100 mm (18–84")	450–1800 mm (18–72")	450–1800 mm (18–72")		
Minimum Pulley Diameter	50 mm (2")	300 mm (12")	300 mm (12")	300 mm (12")	300 mm (12")	300 mm (12")	400 mm (16")	400 mm (16")		
Dry Friction	Very Good	Excellent	Very Good	Very Good	Excellent	Excellent	Very Good	Excellent		
Wet Friction	Average	Average	Good	Very Good	Excellent	Excellent	Good	Excellent		
Wet/Muddy Friction	-	Average	Average	Good	Very Good	Very Good	Average	Very Good		
Wear Life	Good	Good	Good	Very Good	Excellent	Best	Good	Best		
Ease of Installation	Good	Good	Good	Good	Good	Good	Best	Best		
Drainage Grooves	No				Yes					
FRAS (Fire Resistant Anti-Static)	No				Available					
Rubber Compound				SI	BR					
Hardness (Shore A)				68 -	⊦/- 3					
Ceramic Compound	-	-	-	Al_2O_3	Al ₂ O ₃	Al ₂ O ₃	-	Al ₂ O ₃		
Ceramic Coverage	-	-	-	15%	39%	80%	-	74%		
Operating Temperature				-15°–85°C	(5°-185°F)					

*Additional thicknesses and widths available as special orders. For weld-on lagging, thickness includes the backing plate.

			Flex-Lag® Rubber			lex-Lag® Cerami	c	Flex-Lag® Weld-On™			
Criteria		Light Duty	Plain	Diamond	Diamond Pattern	Medium Ceramic	Full Ceramic	Rubber Diamond	Full Ceramic		
	<500 mm (20")	OK	10 mm (3/8")	10 mm (3/8")	12 mm (1/2")	15 mm (5/8")	12 mm (1/2")	ОК	OK		
Pulley Diameter	500–800 mm (20–32")	Non-Drive Only	10–12 mm (3/8–1/2")	10–12 mm (3/8–1/2")	12 mm (1/2")	15 mm (5/8")	12 mm (1/2")	ОК	OK		
Fulley Diameter	800–1200 mm (32–48")	-	12–20 mm (1/2–3/4")	12–20 mm (1/2–3/4")	12– <mark>15 mm</mark> (1/2–5/8")	15 mm (5/8")	12–15 mm (1/2–5/8")	OK	OK		
	>1200 mm (48")		15–25 mm (5/8–1")	15–25 mm (5/8–1")	15–25 mm (5/8–1")	15– <mark>25 mm</mark> (5/8–1")	15–25 mm (5/8–1")	ОК	OK		
	Low (<500 PIW)	OK	10–12 mm (3/8–1/2")	10–12 mm (3/8–1/2")	12 mm (1/2")	15 mm (5/8")	12 mm (1/2")	OK	OK		
Fabric Belts	Medium (500–1000 PIW)	Non-Drive Only	12–15 mm (1/2–5/8")	12-15 mm (1/2-5/8")	12 mm (1/2")	15 mm (5/8")	12 mm (1/2")	OK	OK		
	High (1000–2000 PIW)	-	15–20 mm (5/8–3/4")	15–20 mm (5/8–3/4")	15–25 mm (5/8–1")	15– <mark>25 mm</mark> (5/8–1")	15–25 mm (5/8–1")	-	-		
Steel Cord Belts	Medium (ST500–ST3150)	-	12–20 mm (1/2–3/4")	12-20 mm (1/2-3/4")	12– <mark>20 mm</mark> (1/2–3/4")	15– <mark>20 mm</mark> (5/8– <mark>3/4"</mark>)	12– <mark>20 mm</mark> (1/2– <mark>3/4</mark> ")	-	-		
Steel Cord Belts	High (ST3500-ST5400)	-	20 -30 mm (3/4-1-1/4")	20 -30 mm (3/4 -1-1/4")	15–30 mm (5/8–1-1/4")	15– <mark>30 mm</mark> (5/8–1-1/4")	15–30 mm (5/8–1-1/4")	-	-		

Red items available as specials.

FLEXCO PULLEY LAGGING

Light-Duty Rubber Lagging

- Specially designed for pulleys with diameters as small as 50 mm (2").
- Moisture is channeled between small raised buttons that support and grip the belt and deliver superior traction.
- Available in SBR.



Specifications: Any Belt Width

Diamond Rubber Lagging

- Diamond pattern features a bidirectional design for superior watershedding characteristics.
- Horizontal grooves provide a second method to disperse water and debris off the lagging and prevent hydroplaning.
- Performs well in both dry and wet applications.



Specifications: Any Belt Width

Medium Ceramic Lagging

- 39% tile coverage
- Constructed from individual ceramic tiles molded into a high-durometer rubber for excellent abrasion resistance.
- Excellent performance in dry or wet applications and very good performance in muddy applications.
- Molded ceramic buttons grip the belt's underside for positive traction.
- Excellent friction for mid-range tension belts.



Specifications:

Belt Widths: 450-2100 mm (18-84")

Weld-On™ Rubber Lagging

- Weld-On™ design allows for quick, in-situ installation.
- Gear-tooth layout protects cleaners on pulley from experiencing "chatter" and premature wear.
- Diamond-Pattern features a bidirectional design for superior watershedding characteristics.
- Performs well in both dry and wet applications.



Specifications:

Minimum Pulley Diameter: 400 mm (16") Belt Widths: 450–1800 mm (18–72")

Plain Rubber Lagging

- Helps prevent belt slippage in dry environments.
- · Provides larger surface contact area relative to other patterned lagging.
- Horizontal grooves channel water and debris while providing a better dynamic interaction with the belt compared to sheet lagging.



Specifications: Any Belt Width

Diamond Ceramic Lagging

- 15% tile coverage
- Large ceramic tile is molded into the diamond section, providing an increased coefficient of friction vs. Diamond-Pattern Rubber.
- Features a bidirectional design for superior water-shedding characteristics.
- Uses the advantages of a ceramic product at a more affordable cost in light or medium duty applications.



Specifications: Any Belt Width

Full Ceramic Lagging

- 80% tile coverage
- Constructed from hundreds of individual ceramic tiles molded into a durable rubber backing with a higher coverage than Medium Ceramic for best-in-class abrasion resistance.
- Most consistent performance in dry, wet or muddy applications.
- Molded ceramic buttons grip the belt's underside for positive traction.
- Best for high-tension belts.





Specifications

Belt Widths: 450-2100 mm (18-84")

Weld-On™ Ceramic Lagging

- 74% tile coverage
- Weld-On[™] design allows for quick, in-situ installation.
- Gear-tooth layout protects cleaners on pulley from experiencing "chatter" and premature wear.
- Most consistent performance in dry, wet or muddy applications.
- Molded ceramic buttons grip the belt's underside for positive traction.
- Constructed from hundreds of individual ceramic tiles molded into a durable rubber backing.



Specifications:

Minimum Pulley Diameter: 400 mm (16") Belt Widths: 450–1800 mm (18–72")

FLEXCO PULLEY LAGGING ADHESIVES

Flex-Lag® Adhesives are a two-part cold bonding system designed specifically for use with rubber-to-rubber and rubber-to-metal adhesion. Flex-Lag® Adhesives are also produced without using chlorofluorocarbons (CFCs). An excellent bond is achieved while using the minimal amount of cement and primer thanks to high adhesion during installation and after curing.

Primer specifically paired with the adhesive for optimal bonding strength

Adhesive and activator mix on a 1 can: 1 bottle ratio for simplified ordering, stocking, and preparation



Excellent Bonding Strength

- Simple to order, easy to use
- Environmentally friendly, free of chlorofluorocarbons (CFC)
- Works with all Flexco cold-bond lagging products

Use the following charts to determine correct order quantities for your pulley size.

Each Flex-Lag Adhesive is mixed with one Flex-Lag Activator.
Refer to the usage chart below to calculate the number of cans required for your pulley.
For sizes not included in the chart please contact Flexco Customer Service for assistance.

ADHESIVE 0.8L / ACTIVATOR 40g (1 can : 1 bottle mix ratio)

	Face Width																						
	mm		254	356	457	559	660	762	864	965	1067	1168	1270	1372	1473	1575	1676	1778	1880	1981	2083	2184	2286
		in.	10	14	18	22	26	30	34	38	42	46	50	54	58	62	66	70	74	78	82	86	90
	203	8	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	3	3	3
	305	12	2	2	2	2	2	2	2	2	2	2	2	3	3	3	3	3	3	3	4	4	4
	406	16	2	2	2	2	2	2	2	2	3	3	3	3	3	4	4	4	4	4	5	5	5
	508	20	2	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6	6	6
- a	610	24	2	2	2	2	2	3	3	3	4	4	4	5	5	5	5	6	6	6	7	7	7
Diameter	711	28	2	2	2	2	3	3	3	4	4	5	5	5	6	6	6	7	7	7	8	8	8
jai	813	32	2	2	2	3	3	4	4	4	5	5	6	6	6	7	7	8	8	8	9	9	10
	914	36	2	2	3	3	3	4	4	5	5	6	6	7	7	8	8	8	9	9	10	10	11
Pulley	1016	40	2	2	3	3	4	4	5	5	6	6	7	7	8	8	9	9	10	10	11	11	12
<u> </u>	1118	44	2	2	3	4	4	5	5	6	6	7	7	8	9	9	10	10	11	11	12	12	13
	1219	48	2	3	3	4	4	5	6	6	7	7	8	9	9	10	10	11	12	12	13	13	14
	1321	52	2	3	3	4	5	5	6	7	7	8	9	9	10	11	11	12	13	13	14	15	15
	1422	56	2	3	4	4	5	6	6	7	8	9	9	10	11	11	12	13	14	14	15	16	16
	1524	60	2	3	4	5	5	6	7	8	8	9	10	11	11	12	13	14	14	15	16	17	17

PRIMER .75L

	Face Width																						
	mm		254	356	457	559	660	762	864	965	1067	1168	1270	1372	1473	1575	1676	1778	1880	1981	2083	2184	2286
		in.	10	14	18	22	26	30	34	38	42	46	50	54	58	62	66	70	74	78	82	86	90
	203	8	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	305	12	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	406	16	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	508	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
-	610	24	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Diameter	711	28	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
jar	813	32	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
,	914	36	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2
Pulley	1016	40	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2
ه ا	1118	44	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
	1219	48	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2
	1321	52	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
	1422	56	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	2
	1524	60	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	2	2

FLEXCO SERVICES



Inspection, Installation and Maintenance

Around the world, Flexco has your operation covered. Whether it be with our factory-trained and certified Flexco resources or our trained distributor partners, we're there to ensure you maximize the return on your investment by making sure Flexco's products are properly specified, installed, or maintained.

Ensuring the product is installed correctly and maintained is critical to provide the optimal results our products are engineered to deliver. Flexco takes pride in making sure you have access to the resources that make certain the products exceed your expectations.



Conveyor Assessments

Having a third party review your conveyor system can prove to be an effective way to identify performance, maintenance and safety concerns that can be critical to minimizing downtime and maximizing your productivity.

Flexco's assessment program allows you to proactively address belt conveyor concerns before they lead to costly repairs and unscheduled downtime. Focusing on issues such as spillage, carryback, belt slippage, and mistracking, Flexco specialists will record their findings and return to your operation with a complete recommendation on the system, identifying immediate needs and suggesting future fixes.







Training

Flexco offers training programs around the world that are flexible to meet your needs and requirements. Our programs range from coming to your site to train a maintenance team to hosting you at one of our Flexco training centers at 10 locations around the world. Our comprehensive Flexco University program delivers the knowledge and skills required to ensure you keep your belts running effectively and efficiently, balancing both classroom and field instruction to deliver a detailed, thorough education program. We utilize a variety of tools, from mobile showrooms to demonstration conveyors to provide the most value.





TRUST YOUR PARTNERS IN PRODUCTIVITY

Flexco's *Partners Plus* distributors are strategic partners that have been certified to provide unsurpassed quality installations and service to complement the industry's leading products. Partners Plus Distributors are also certified by Flexco to diagnose problems, recommend solutions, and share advanced knowledge that will help operations maintain their belt conveyor systems and maximize efficiency and output.

Fewer than 5% of all Flexco distributors are Authorized Partners Plus distributors, making this a special distinction given to distributors who have committed to providing the skills required to earn this title. To obtain this certification, employees from our distributor partners undergo extensive training, learning to properly specify, install, maintain, and troubleshoot Flexco products. Continual training is offered throughout the year to ensure they are fully up to speed on Flexco's offerings and latest innovations. Each partner is recertified each year they are in the program.

Our Partners Plus distributors are easily identified by looking for this logo on our website's distributor locator. With over 30 partners in over 15 countries, this growing program that partners Flexco with local experts and the operations in their regions allows us to work together to address their productivity needs.



We work with you to determine the best solution.

Partners Plus distributors are trained to be experts on specifying, installing, and troubleshooting Flexco products, to ensure you receive the optimal performance from your investment.



We have extensive industry knowledge.

Our hands-on industry experience gives us deep insights into your productivity demands, maintenance challenges, safety requirements, and more. We serve operations all over the world in the coal, aggregate, bulk material, and mining industries. Our global presence balanced with the expertise of our local Partners Plus distributors allows us to enhance the service you receive, actively working toward addressing your specific concerns and needs that may be unique to your operation or industry.



We're committed to safety and quality.

At Flexco, we won't settle for anything less than the best, most durable products around, and we aim to have the services and support to match. That is why we developed the Partners Plus program—to deliver a quality and consistent service program capable of matching the quality of our products.

Just as our products are designed with safety in mind, our training with our Partners Plus distributors always makes safety a top priority.




We offer a wide range of compatible products.

In addition to high-quality belt conveyor products, through our Partners Plus program we also deliver high quality support and service that matches those products.













Visit our website or contact your local distributor to learn more.



Visit www.flexco.com for other Flexco locations and products, or to find an authorized distributor.



